

## Løvvang daglig 2324



Oil Pattern Distance Forward Oil Total Tank Configuration

14.77 mL Multi Tank

39

Reverse Brush Drop Reverse Oil Total Tank A Conditioner

8.74 mL CURRENT

36

Oil Per Board Volume Oil Total Tank B Conditioner Multi ul 23.51 mL ICE

	START	STOP	LOADS	MICS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	2	50	14	3	В	74	0.0	1.9	1.9	3700
2	2L	4R	1	50	14	3	В	35	1.9	3.8	1.9	1750
3	6L	5R	1	50	14	3	В	30	3.8	5.7	1.9	1500
4	7L	6R	2	45	18	3	Α	56	5.7	10.8	5.1	2520
5	8L	7R	2	45	18	3	Α	52	10.8	15.9	5.1	2340
6	9L	8R	2	45	18	3	Α	48	15.9	21.0	5.1	2160
7	11L	10R	1	40	18	3	Α	20	21.0	23.5	2.5	800
8	2L	2R	0	40	22	3	Α	0	23.5	32.0	8.5	0
9	2L	2R	0	40	26	3	Α	0	32.0	35.0	3.0	0
10	2L	2R	0	40	26	2	Α	0	35.0	39.0	4.0	0

	START	STOP	LOADS	MICS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	50	30	3	Α	0	39.0	24.0	-15.0	0
2	12L	11R	1	45	22	3	Α	18	24.0	20.9	-3.1	810
3	11L	9R	1	45	22	3	Α	21	20.9	17.8	-3.1	945
4	10L	8R	1	45	22	3	Α	23	17.8	14.7	-3.1	1035
5	9L	7R	1	50	18	4	В	25	14.7	12.2	-2.5	1250
6	8L	5R	1	50	18	4	В	28	12.2	9.7	-2.5	1400
7	5L	5R	1	50	18	4	В	31	9.7	7.2	-2.5	1550
8	2L	4R	1	50	14	4	В	35	7.2	5.3	-1.9	1750
9	2L	2R	0	50	14	3	В	0	5.3	0.0	-5.3	0

Cleaner Ratio Main Mix 5:1
Cleaner Ratio Back End Mix 5:1
Cleaner Ratio Back End Distance 59
Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

5:1 Forward5:1 Reverse59 Combined



Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	3.15	1.19	1	1	1.07	2.53



